



PLC-XP100L

- Brightness: 6,500 ANSI lumens, contrast ratio: 2,000 : 1
- Inorganic 3LCD panels for superior colour quality and image homogeneity
- Network integration (optional) with control camera
- Automatic air filter replacement reduces maintenance frequency
- A horizontal and vertical lens shift function makes flexible positioning a lot easier
- Very quiet: 32 dB (eco mode)
- 6 interchangeable lenses
- 3 years warranty

PLC-XPI00L

TECHNICAL DETAILS	PLC-XPI00L
Category	Professional
Panel	3 x 1.3" TFT p-Si (4 : 3), micro lens
Lamp	330 W NSHA (LMP-108)
Brightness ANSI lumens	6,500
Lamp Service Life	3,000 h (eco mode), 2,000 h (normal mode)
Fan Noise	32 dB (eco mode), 40 dB (normal mode)
Standard Lens	Delivery without lens
Throw Distance Ratio	Depending on lens
Throw Distance	Depending on lens
Contrast Ratio	2,000 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min-max (diagonal)	31"-400"
Uniformity	90 %
Bandwidth/Frequency	180 MHz, horizontal 15-100 kHz, vertical 48-100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: DVI-D (digital/HDCP) Input 2: D-Sub15 (RGB/SCART-RGB), D-Sub 15 monitor output Input 3: 5 x BNC (RGBHV/Video/Y-Pb/Cb-Pr/Cr) Input 4: 3 x RCA (Video/Y-Pb/Cb-Pr/Cr), Mini DIN 4-pin (S-Video) Control Input Jack 1: D-Sub9 (RS232) Control Input Jack 2: USB type B (Mouse Control) Control Input Jack 3: 3.5 mm Stereo Jack (cable remote control)
Keystone Correction	vertical +/-40°, horizontal +/-20°
Lens-Shift	10 : 0 to 1 : 1 vertical (for LNS-S31/LNS-W31A/LNS-T31A/LNS-T32) 1 : 1 vertical (applies to LNS-W32) 2 : 3 to 3 : 2 horizontal (applies to LNS-S31/W31A/T31A/T32) 1 : 1 horizontal (applies to LNS- W32)
HDTV Signals	1,080i, 1,035i, 720p, 480p
Computer Compatibility	UXGA/SXGA/SXGA+/WXGA/XGA/SVGA/VGA
Zoom/Focus	Depending on lens
Power Consumption/Voltage	392 W (eco mode)/490 W (normal mode)/100-240 V
Warranty	3 years
Dimensions (W x H x D)	370 x 187 x 440 mm
Weight	11.7 kg (without lens)
Standard Accessories	IR remote control with mouse function, batteries, user manual (CD-ROM), power cable, D-Sub 15 cable, computer cable (D-Sub 15/D-Sub 15), PIN code label, light-block sheet, lens adapter
Optional Accessories	PJ Net Organizer Plus (POA-PN03), PJ Net Organizer Plus with video camera (POA-PN03C)
Lenses	Optional Standard Lens: LNS-S31 (Throw distance ratio: 1.8-2.4 : 1) Optional Standard Lens: LNS-S30 (Throw distance ratio: 1.8-2.4 : 1) Optional Wide Angle Lens: LNS-W31A (Throw distance ratio: 1.23-1.78 : 1) Optional Wide Angle Lens: LNS-W32 (Throw distance ratio: 0.81 : 1) Optional Telephoto Lens: LNS-T31A (Throw distance ratio: 2.31-4.19 : 1) Optional Telephoto Lens: LNS-T32 (Throw distance ratio: 4.2-6.0 : 1)

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007



Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: www.sanyo.co.uk