

XEROX®

Technology | Document Management | Consulting Services

black-and-white laser printer

The compact printer that makes a big impression



Call today. For more information, call **1-877-362-6567** or visit us at **www.xerox.com/office**



		Phaser 5335
Speed		Up to 35 ppm
Duty Cycle		100,000 pages / month
Paper Handling		
Paper input	Standard	Tray 1 (MPT): 150 sheets; Custom sizes: 3 x 5.8 in. to 11.7 x 17 in. / 75 x 148 mm to 297 x 431 mm
		Tray 2: 550 sheets; Custom sizes: 3 x 5.8 in. to 11.7 x 17 in. / 75 x 148 mm to 297 x 431.8 mm
	Optional	Tray 3 – 5: 550 sheets; Custom sizes: 3 x 5.8 in. to 11.7 x 17 in. / 75 x 148 mm to 297 x 431.8 mm (up to three can be added)
Paper output		250 sheets
Two-sided output		Optional
Print		
First-page-out time		As fast as 9.5 seconds
Resolution (max)		1200 x 1200 dpi
Processor		400 MHz
Memory (std / max)		64 MB / 576 MB
Connectivity		10/100Base-TX Ethernet, Parallel, USB 2.0
Page Description Languages		Adobe® PostScript® 3™, PCL®5e emulation, PCL 6 emulation, ESC / P
Print features	Standard	Custom-size pages, Banner-size (11.7 x 35.4 in. / 297 x 900 mm), Booklet printing, Poster printing, Edge-to-edge printing, Scaling, Watermarks, Covers, Separators, N-up, Load-while-run, Job accounting
	Optional	Hard Drive Kit (minimum 40 GB): Secure/Proof Print, Hard disk collation, Extended font storage, limited PDF-direct printing
Warranty		One-year on-site warranty, Xerox Total Satisfaction Guarantee

Device Management

CentreWare® IS Embedded Web Server

Print Drivers

Windows® 2000/XP/2003 Server, NT 4.0, Vista, Mac OS® X version 10.3.9 or higher, Red Hat® Enterprise Linux WS version 4, Turbolinux 10F, SUSE Linux 9.3 Professional, SUSE Linux 10.1

Font Capability

PostScript® fonts: 136; PCL® fonts: 81

Media Handling

Trays 1–5: 60–216 gsm
Two-sided output: 60–190 gsm
Media types: Plain paper, envelopes, labels, transparencies, card stock

Operating Environment

Temperature: 41° to 90°F / 5° to 32°C
Humidity: 15% to 85%
Sound power: Printing: 7.1 B, Standby: 5.3 B
Warm-up time (from power save): 16 seconds or less, FPOT from power save: as fast as 10 seconds

Electrical

Power: 220–240 VAC, 50/60 Hz
Power consumption: Printing: 470 W or less, Standby: 105 W, Power save: 5 W, ENERGY STAR® qualified

Dimensions (WxDxH)

18.1 x 19.9 x 14.8 in. / 459 x 506 x 375.3 mm
Weight w/ consumables: 52.2 lb. / 23.5 kg
Weight w/o consumables: 47.3 lb. / 21.3 kg

Certifications

FDA/CDRH – Class 1 Laser Product, CE marked, Low Voltage Directive 73/23/EEC, EN 60950-1, 1st Edition, EN 60825-1 – Class 1 Laser Product, EMC Directive 89/336/EEC, EN 55022, Class B, EN 55024, RoHS Directive 2002/95/EC, WEEE Directive 2002/96/EC

Supplies

Print Cartridge: 113R00737
10,000 pages¹

Routine Maintenance Items

Maintenance Kit, 220V: 108R00772
100,000 pages²

Options

Hard Drive Kit 098S05006
Duplex Module 097S03871
550-Sheet Feeder 097S03870
256 MB Phaser Memory 098S05021
512 MB Phaser Memory 098S05022
Multi-Protocol Network Card 098S05007
Wireless LAN 220 V 097S03741



Standard 150-sheet Tray 1

Standard 550-sheet Tray 2

Optional: 3 additional 550-sheet feeders

¹Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

²Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.

