

# WorkCentre® 3550

## Black-and-White Multifunction Printer



### WorkCentre 3550

A value-driven performer that offers printing, copying, faxing and scanning.

WorkCentre 3550	
<b>Output Speed</b>	
<b>Single-Sided</b>	Up to 35 ppm 8.5 x 11 in. Up to 33 ppm A4 (210 x 297 mm)
<b>Automatic Two-Sided</b>	Up to 18 ppm 8.5 x 11 in. Up to 18 ppm A4 (210 x 297 mm)
Paper Handling - Input	
<b>Duplex Automatic Document Feeder</b>	
<b>Capacity<sup>1</sup></b>	60 sheets
<b>Sizes</b>	Custom Sizes: 2.75 x 5.7 in. to 8.5 x 14 in. to 8.5 x 14 in / 69.9 x 145 mm to 216 x 356 mm
<b>Weights</b>	12 lb. bond to 28 lb. bond (50 to 120 gsm)
Multipurpose Tray	
<b>Capacity<sup>1</sup></b>	50 sheets
<b>Sizes</b>	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. (76 x 127 mm to 216 x 356 mm)
<b>Weights</b>	16 lb. bond to 43 lb. bond (60 to 163 gsm)
<b>Media Types</b>	Plain paper Letterhead Bond Heavyweight Lightweight Recycled Archive Labels Drilled Postcard Transparencies Envelopes Custom 1-7

<sup>1</sup> Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

<b>Main Tray</b>	
Capacity <sup>1</sup>	500 sheets
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 28 lb. bond (60 to 105 gsm)
Media Types	Plain paper Heavyweight Lightweight Recycled Archive Letterhead Drilled
<b>Additional Tray (Optional)</b>	
Capacity <sup>1</sup>	500 sheets
Sizes	Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 28 lb. bond (60 to 105 gsm)
Media Types	Plain paper Heavyweight Lightweight Recycled Archive Letterhead Drilled
<b>Paper Handling - Output</b>	
Standard Output	250 sheets
<b>Print</b>	
First-Page-Out-Time	As fast as 8.5 seconds
Print Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Memory (Std/max)	256 MB / 512 MB
Processor	360 MHz
Language Support	Postscript® 3™ compatibility PCL® 5e emulation PCL® 6 emulation
Connectivity	10/100 Base-TX Ethernet, USB 2.0
Printing Features	Automatic two-sided printing Custom page size Toner save mode Proof print Secure print Watermarks N-up Fit to page Overlay Reduce/Enlarge Poster Scaling Booklet printing Print from USB memory device

<sup>1</sup> Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

<b>Print Drivers</b>	Windows® XP (32/64bit) / 2003 (32/64bit) / 2008 Server (32/64 bit) / Vista (32/64bit) / Windows 7 (32/64bit) / 2008 R2 (64bit) Macintosh® OS X v10.3-10.6 RedHat Enterprise Linux WS 4, 5 (32/64bit) Fedora Core 2-10 (32/64bit) SuSE Linux 9.1 (32bit) OpenSuSE 9.2, 9.3, 10.0, 10.1, 10.2 10.3, 11.0, 11.1 (32/64bit) Mandrake 10.0, 10.1 (32/64bit) Mandriva 2005, 2006, 2007, 2008 (32/64bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10 (32/64bit) SuSE Linux Enterprise Desktop 9, 10 (32/64bit) Debian 3.1, 4.0, 5.0 (32/64bit) Xerox® Mobile Express Driver™ Xerox® Global Print Driver®
<b>Font Capability</b>	136 PostScript® fonts 111 PCL® fonts
<b>Copy</b>	
<b>Document Scanner</b>	Duplex Automatic Document Feeder with 60-sheet capacity
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 999
<b>Resolution</b>	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
<b>Concurrency</b>	Concurrent scanning and printing
<b>First-Copy-Out-Time</b>	As fast as 10 seconds
<b>Copy Features</b>	Automatic two-sided Reduce/Enlarge Background Suppression Collation (DADF only) ID Card Copy N-up (2-up/4-up) Book copy Booklet creation Clone copy (Platen only) Poster copy (Platen only)
<b>Foreign Device Interface (Optional)</b>	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service
<b>Fax</b>	
<b>Embedded Fax, PC Fax (1 line)</b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Memory</b>	Up to 7 MB
<b>Resolution</b>	Up to 600 x 600 dpi (superfine) resolution
<b>Compression</b>	MH, MR, MMR, JPEG and JBIG

<b>Fax Features</b>	<p>Color fax send                  Two-sided                  Fax forward to Fax/Email and Server (FTP, SMB)                  PC Fax (send only)                  Secure fax receive                  Searchable address book                  Auto redial                  Last number redial                  Pause                  Distinctive ring                  External phone interface                  Journal                  Confirmation reports                  Auto dial list                  Junk fax barrier                  Persistent Flash Memory                  Up to 209 group dial locations                  Broadcast fax                  Delayed fax                  Memory receive                  Auto file size reduction</p>
<b>Scan</b>	
<b>Capability</b>	Black-and-white, grayscale and color scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Input Speed</b>	Scan at 35 ipm (images per minute) black-and-white (8.5 x 11) / 33 ipm (A4) Scan at 24 ipm color (8.5 x 11) / 22 ipm (A4) @ 300 dpi
<b>Resolution</b>	300 x 300 dpi 200 x 200 dpi 100 x 100 dpi
<b>Maximum Scan Area</b>	8.6 x 11.9 in. / 219 x 303 mm
<b>Network Protocol</b>	FTP SMTP SMB
<b>File Formats</b>	JPG PDF TIFF Multipage TIFF
<b>Supported Scan Destinations</b>	Scan to Email (includes support for Global Address Book via LDAP and up to 200 local address book entries) Network Scan to PC Scan to FTP and SMB Direct Scan to Applications, including OCR (software included) Scan to USB memory device
<b>Scanning Solutions</b>	
<b>Scan to PC Desktop® Personal Edition</b>	<ul style="list-style-type: none"> <li>• A desktop and server-based offering that provides document imaging, archiving, editing and organization tools</li> <li>• Nuance® PaperPort SE 11.0 – image viewing and file management software</li> <li>• OmniPage® 16 SE (for desktop/client installation) – OCR and file format conversion software</li> <li>• Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops</li> </ul>
<b>Security</b>	

<b>Security Features</b>	802.1x Kerberos SNMPv3 HTTPS Secure Fax SSL IPv6 LDAP IP Filtering Scan to Email with authentication
<b>Device Management</b>	
<b>Xerox CentreWare® Web</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic Accounting and asset management</li> </ul>
<b>Xerox CentreWare® Internet Services - Integrated Device Web Page</b>	
<b>Device Status</b>	Web server embedded <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management
<b>Job Submission</b>	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Netscape® 6.2 Netscape® 7.x (Mozilla 1.x) Netscape® 8.x Microsoft® Internet Explorer 5.5.x, 6.x, 7.x Apple® Safari™ 1.2.x, 2.x Firefox® 1.5.x, 2.x
<b>Device Specifications</b>	
<b>Duty Cycle</b>	
	Up to 75,000 pages / month <sup>2</sup>
<b>Electrical Requirements</b>	
	220-240 VAC, 50/60 Hz 110-127 VAC, 50/60 Hz ENERGY STAR® qualified
<b>Power Consumption</b>	
<b>Printing</b>	600 watts
<b>Standby</b>	<60 watts
<b>Power save</b>	<20 watts
<b>Warm up (from sleep mode)</b>	<15 seconds
<b>Operating Temperature Range</b>	50° to 90° F (10° to 32° C)

<sup>2</sup> Print volume uniformly distributed over 30 days

# WorkCentre® 3550

<b>Relative Humidity Range</b>	20 % to 80 %			
<b>Sound Pressure Levels</b>				
<b>Printing</b>	55 dB(A)			
<b>Standby</b>	39 dB(A)			
<b>Dimensions and Weights</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>Product</b> (without print cartridge)	22.9 in. / 582 mm	19.2 in. / 488 mm	21.8 in. / 553 mm	51.59 lbs / 23.4 kg
<b>Package</b>	26.6 in. / 676 mm	24.3 in. / 619 mm	27.4 in. / 696 mm	65.48 lbs / 29.7 kg
<b>Certifications</b>				
	Listed UL 60950 CE Mark applicable to Directives 2006/95/EC 2004/108/EC and 99/5/EC, FCC Part 15 Class A, FCC Part 68 ENERGY STAR® qualified			
<b>What Comes in the Box</b>				
	<ul style="list-style-type: none"> <li>• WorkCentre 3550 Multifunction Printer</li> <li>• Print cartridge (5,000 print capacity)</li> <li>• World Kit CD (includes Printer Installer, utilities, Software and documentation)</li> <li>• Power cord</li> <li>• Fax cord</li> </ul>			
<b>Supplies and Options</b>	<b>Description</b>	<b>Order Number</b>		
	High-Capacity Print Cartridge – approximately 11,000 standard pages <sup>3</sup>	106R01530		
	Standard-Capacity Print Cartridge – approximately 5,000 pages <sup>3</sup>	106R01528		
	500-sheet Tray	098N02190		
	256 MB Memory Upgrade	098N02189		
	Stand	097N01674		
	Foreign Device Interface	097N01676		
	Wireless Network Adapter	097N03740		

<sup>3</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used.



For more information, call **1-877-362-6567** or visit us at [www.xerox.com/office](http://www.xerox.com/office)

©2010 Xerox Corporation. All rights reserved. XEROX® and XEROX and Design®, CentreWare® and WorkCentre® are trademarks of or licensed to Xerox Corporation in the United States and/or other countries. Adobe® and PostScript® 3™ are registered trademarks or trademarks of Adobe Systems, Incorporated PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR® partner Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy 6/10 610P730057 W3B5S-01UA